

APPLICATION DATA SHEET

Electronic Version 0.0.11

Stylesheet Version: 1.0

Attorney Docket Number: INE-0044-C2

Publication Filing Type: new-utility

Application Type: utility

Title of Invention: FLEXIBLE SOURCE WIRE FOR RADIATION

Attorney Docket Number: INE-0044-C2

Suggested Representative Figure: Figure 1

Legal Representative:

Attorney or Agent: Mr. HERBERT M. BEDINGFIELD

Registration Number: 44530

Customer Number Correspondence Address: 23413



Continuity Data:

This application is a continuation of 09/455,579 1999-12-06 US co-pending application
which is a division of 80/827,787 1997-04-11 co-pending application
which is a division of 08/480,307 1995-06-07 patent granted
which is a continuation in part of 08/257,045 1994-06-08 patent granted

INVENTOR(s):

Primary Citizenship: US

Given Name: SAM

Middle Name: F.

Family Name: LIPRIE

Residence City: LAKE CHARLES

Residence State: LA

Residence Country: US

Address: ONE GORHAM ISLAND
WESTPORT CT, 06880
203-341-9800

Table 1. Demographic characteristics of the study population	
Age (years)	Mean (SD)
18-24	20.5 (2.5)
25-34	29.5 (4.5)
35-44	39.5 (5.5)
45-54	49.5 (6.5)
55-64	59.5 (7.5)
65-74	69.5 (8.5)
75-84	79.5 (9.5)
85-94	89.5 (10.5)
95-104	99.5 (11.5)
105-114	109.5 (12.5)
115-124	119.5 (13.5)
125-134	129.5 (14.5)
135-144	139.5 (15.5)
145-154	149.5 (16.5)
155-164	159.5 (17.5)
165-174	169.5 (18.5)
175-184	179.5 (19.5)
185-194	189.5 (20.5)
195-204	199.5 (21.5)
205-214	209.5 (22.5)
215-224	219.5 (23.5)
225-234	229.5 (24.5)
235-244	239.5 (25.5)
245-254	249.5 (26.5)
255-264	259.5 (27.5)
265-274	269.5 (28.5)
275-284	279.5 (29.5)
285-294	289.5 (30.5)
295-304	299.5 (31.5)
305-314	309.5 (32.5)
315-324	319.5 (33.5)
325-334	329.5 (34.5)
335-344	339.5 (35.5)
345-354	349.5 (36.5)
355-364	359.5 (37.5)
365-374	369.5 (38.5)
375-384	379.5 (39.5)
385-394	389.5 (40.5)
395-404	399.5 (41.5)
405-414	409.5 (42.5)
415-424	419.5 (43.5)
425-434	429.5 (44.5)
435-444	439.5 (45.5)
445-454	449.5 (46.5)
455-464	459.5 (47.5)
465-474	469.5 (48.5)
475-484	479.5 (49.5)
485-494	489.5 (50.5)
495-504	499.5 (51.5)
505-514	509.5 (52.5)
515-524	519.5 (53.5)
525-534	529.5 (54.5)
535-544	539.5 (55.5)
545-554	549.5 (56.5)
555-564	559.5 (57.5)
565-574	569.5 (58.5)
575-584	579.5 (59.5)
585-594	589.5 (60.5)
595-604	599.5 (61.5)
605-614	609.5 (62.5)
615-624	619.5 (63.5)
625-634	629.5 (64.5)
635-644	639.5 (65.5)
645-654	649.5 (66.5)
655-664	659.5 (67.5)
665-674	669.5 (68.5)
675-684	679.5 (69.5)
685-694	689.5 (70.5)
695-704	699.5 (71.5)
705-714	709.5 (72.5)
715-724	719.5 (73.5)
725-734	729.5 (74.5)
735-744	739.5 (75.5)
745-754	749.5 (76.5)
755-764	759.5 (77.5)
765-774	769.5 (78.5)
775-784	779.5 (79.5)
785-794	789.5 (80.5)
795-804	799.5 (81.5)
805-814	809.5 (82.5)
815-824	819.5 (83.5)
825-834	829.5 (84.5)
835-844	839.5 (85.5)
845-854	849.5 (86.5)
855-864	859.5 (87.5)
865-874	869.5 (88.5)
875-884	879.5 (89.5)
885-894	889.5 (90.5)
895-904	899.5 (91.5)
905-914	909.5 (92.5)
915-924	919.5 (93.5)
925-934	929.5 (94.5)
935-944	939.5 (95.5)
945-954	949.5 (96.5)
955-964	959.5 (97.5)
965-974	969.5 (98.5)
975-984	979.5 (99.5)
985-994	989.5 (100.5)
995-1004	999.5 (101.5)
1005-1014	1009.5 (102.5)
1015-1024	1019.5 (103.5)
1025-1034	1029.5 (104.5)
1035-1044	1039.5 (105.5)
1045-1054	1049.5 (106.5)
1055-1064	1059.5 (107.5)
1065-1074	1069.5 (108.5)
1075-1084	1079.5 (109.5)
1085-1094	1089.5 (110.5)
1095-1104	1099.5 (111.5)
1105-1114	1109.5 (112.5)
1115-1124	1119.5 (113.5)
1125-1134	